

Dynatex[®]

Automotive

Automotive

Industrial

Industrial

Fastener

Fastener

Ag

Ag

ATV

ATV

Marine

Marine

Motorcycle

Motorcycle

Heavy Duty

Heavy Duty

Dynatex

350 Ring Road
Elizabethtown, KY 42701
Phone (800) 999-2937
Fax (270) 769-6418

REGIONAL OFFICE

988 Chetford Drive
Lexington, KY 40509
Phone (859) 263-2326
Fax (859) 263-0882

ASIA OFFICE

#18 Kitpanit Bldg. 5th Floor
#502 Patpong Road
Suriyawong, Bangrak
Bangkok, 10500 Thailand
Phone (662) 634-3060
Fax (662) 634-3066

DUBAI OFFICE

Al Meer Tower, Flat #1103
Dubai, United Arab Emirates
Phone +971 55 3792633
Fax +9714 4318529

INDIA OFFICE

No: 245, GST Road
Urapakkam, PIN-603202
Kancheepuram District
Tamilnadu, India
Phone +91 44 30060346-51
Fax +91 44 30060345

Visit us on the worldwide web at
www.dynatexinc.com

Email: sales@dynatexinc.com



Table of Contents

Dyna Series Gasket Makers Pg. 3

DynaGrey Silicone Gasket Maker
DynaBlack Silicone Gasket Maker
DynaPlus Fast Cure Gasket Maker

Traditional Gasket Makers Pg. 4

Black Silicone Gasket Maker
Red Hi-Temp Silicone Gasket Maker
Blue Silicone Gasket Maker
Clear Silicone Adhesive Sealant

Sealants / Adhesives Pg. 5

Industrial Grade Silicones
Hi-Tack Gasket Spray
Gasket Remover

Repair Adhesives Pg. 6-7

Auto Seam Sealant
Rear View Mirror Adhesive
4-Minute Epoxy
Muffler & Tailpipe Sealant
GTX Multi-Seal™ Trailer Sealant
Black Brush-On Electrical Tape
Black Weatherstrip
Yellow Weatherstrip

Super Glue Adhesives Pg. 8

Super Glue
Super Glue Gel
Rubber Toughened Adhesive
Clear Rubber Bonder

Anaerobic Threadlockers Pg. 9-10

Blue Medium Strength
Red High Strength
Green High Strength
Purple Low Strength
Green High Strength Sleevelocker
Threadlocker Gel
Anaerobic Gasket Maker
Threadlocker Primer

Pipe / Thread Sealants Pg. 11

Pipe Sealant
Thread Sealant

Lubricants Pg. 12

Aluminum Anti-Seize
Copper Anti-Seize
Nickel Anti-Seize
Silicone Spray Lubricant
Transmission Assembly Lube

Specialty Greases Pg. 13

Red Grease
Dielectric Grease
White Lithium Grease
Motor Assembly Grease
Heat Transfer Compound
Wheel Bearing Assembly Lube

Brake Maintenance Pg. 14

Brake & Caliper Lubricant
Ceramic Disc Brake Grease
Disc Brake Quiet
Non-Chlorinated Brake & Parts Cleaner

Aerosols Pg. 15-16

Battery Terminal Cleaner w/Acid Detector
Battery Terminal Protector
Carb & Choke Cleaner
Penetrating Oil
Electrical Parts Cleaner
Contact Cleaner
Glass Cleaner
Engine Degreaser
Rubberized Undercoating
Belt Dressing

Hand Cleaners Pg. 17

Dual Sided Abrasive Hand Wipes
Biodegradable Hand Wipes
Hand Cleaner w/Lanolin

Hand Cleaners



Dual Sided Abrasive Hand Wipes

Remove the toughest grease, tar, silicone, ink, paint and adhesives. Each pre-moistened wipe has a textured surface on one side that is ideal for cleaning heavily soiled hands. The dual sided wipes have a pleasant scent with moisturizing formula to help keep hands from cracking.



Biodegradable Hand Wipes

Dynatex offers a Green Solution to cleaning. The biodegradable hand wipes are 100% compostable and made without harmful chemicals. Each pre-moistened wipe is made of all natural fabric that has been engineered for softness and absorbency.

Removes:

- Grease
- Tar
- Silicone
- Ink
- Paint
- Adhesives



Hand Cleaner with Lanolin

Dynatex Hand Cleaner with Lanolin is a creamy formula that liquefies and gently lifts grease and stains from the hands with or without water. Leaves hands cleaned and conditioned without the greasy feeling and strong odors of competitive brands. Helps in healing of rough, dry and overused hands. Pumice free.



Ordering Information

Dynatex Part No.	Description & Size	Units Per Case
53103	Biodegradable Wipes - 72 - 8" x 12" Wipes	8
53104	Dual Sided Abrasive Wipes - 80 - 8" x 12" Wipes	8
53107	Hand Cleaner with Lanolin - 18 - 15 Oz. Bottles with Display Rack	18
53108	Hand Cleaner with Lanolin - 15 Oz. Squeeze Bottle	12



Why Dynatex?

- 40 Years of Experience
- ISO Certified
- Manufacturer & Packager
- Private Label Capability
- Old Fashioned Personal Customer Service
- 24 Hour Order Turnaround
- Made in U.S.A.
- Most Important . . . MORE PROFITS!!!!

Dyna Series Gasket Makers

Formulated for Late Model Vehicles



DynaGrey RTV Silicone Gasket Maker
O² Sensor Safe
Formulated for import cars. Use to replace most gaskets. High temperature, sensor safe, low odor and non-corrosive. Resists water, oil and antifreeze. Will not leak. Temperature resistant up to 500°F (260°C). Use on valve covers, oil pans, water pumps, transmission pans, thermostat housings, timing covers and intake manifold end seals.
(82194/85084 Permatex® Ultra Grey® functional equivalent)

DynaBlack RTV Silicone Gasket Maker
O² Sensor Safe
Excellent oil resistance, guaranteed not to leak. Leak proof in the presence of oil, water and anti-freeze. Sensor safe and manufactured to meet OEM specifications. Makes instant gaskets for all engines. Temperature resistant up to 500°F (260°C). Use on valve covers, oil pans, transmission pans, timing covers and intake manifold end seals.
(82180/82080 Permatex® Ultra Black® functional equivalent)

DynaPlus Fast Cure Gasket Maker
O² Sensor Safe
A “thicker” elastomeric rubber used by technicians to replace cut gaskets. DynaPlus is manufactured to meet or exceed OEM specs as well as being O² Sensor Safe. Designed to provide increased resistance to oil, water, anti-freeze, transmission fluid and many other shop fluids. DynaPlus offers greater gasket “blowout” resistance and problems due to vibration. Applications include valve covers, transmission pans, oil pump flanges, timing gear and differential covers, water pumps and much more.
(29208/85224 Permatex® Right Stuff® functional equivalent)



Ordering Information

Dynatex Part No.	Description & Size	Units Per Case
47181	DynaGrey Silicone Gasket Maker - L/V - O ² Safe - 3 Oz. (85gm) Tube - Carded	12
47182	DynaGrey Silicone Gasket Maker - L/V - O ² Safe - 8 Oz. Automatic Can	12
47200	DynaBlack Silicone Gasket Maker - L/V - O ² Safe - 3 Oz. (85gm) Tube - Carded	12
47201	DynaBlack Silicone Gasket Maker - L/V - O ² Safe - 8 Oz. Automatic Can	12
47205	DynaPlus Fast Cure Black Gasket Maker - O ² Safe - 5 Fl. Oz. Cartridge	6
47206	DynaPlus Fast Cure Black Gasket Maker - O ² Safe - 6.75 Oz. Trigger Can	6

Aerosols



Engine Degreaser
Penetrating formula produces quick, satisfying results. Ideal for dissolving grease, oil and dirt deposits on engines of all types. Can also be used on driveways and garage floors. Cleans off easily to restore bright appearance to engines, machinery and more.

Glass Cleaner
Non-streaking formula cuts through stubborn dirt and film without smudging. Removes tar, road film, insects, salt, grease and paint overspray from glass. Also can be used on mirrors, chrome, porcelain, stainless steel and other hard surfaces. Ammonia free.

Rubberized Undercoating
Provides long-lasting rust and corrosion protection to the undercarriage of cars, trucks, buses and trailers. Resilient rubber texture is tough and flexible with sound deadening qualities. Rubberized for maximum thickness, durability and flexibility.

Belt Dressing
Extends belt life by conditioning against drying and cracking. Stops squeal and protects against belt slippage due to heat, cold, dampness, dust and glazing. Penetrates the cord fibers to restore pliability and flexibility. Recommended for use on all types of machinery and equipment with motor-driven belts.

Ordering Information

Dynatex Part No.	Description & Size	Units Per Case
49675	Battery Terminal Cleaner w/Acid Detector - 16 Oz. Aerosol Can - 15 Oz. Net Wt.	12
49678	Battery Terminal Protector - 16 Oz. Aerosol Can - 12.25 Oz. Net Wt.	12
52105	Carb & Choke Cleaner - 16 Oz. Aerosol Can - 12 Oz. Net Wt.	12
52125	Penetrating Oil - 16 Oz. Aerosol Can - 12 Oz. Net Wt.	12
52145	Electrical Parts Cleaner - 16 Oz. Aerosol Can - 16 Oz. Net Wt.	12
52146	Contact Cleaner - 16 Oz. Aerosol Can - 12 Oz. Net Wt.	12
52165	Engine Degreaser - 20 Oz. Aerosol Can - 16 Oz. Net Wt.	12
52175	Rubberized Undercoating - 20 Oz. Aerosol Can - 16 Oz. Net Wt.	12
52185	Glass Cleaner - 20 Oz. Aerosol Can - 19 Oz. Net Wt.	12
52188	Belt Dressing - 16 Oz. Aerosol Can - 12 Oz. Net Wt.	12

Aerosols



Battery Terminal Cleaner w/Acid Detector

Use for cleaning all types of storage batteries and attachments in vehicles and emergency power supply systems. Penetrates and removes corrosion, dirt and grime instantly. Detects corrosion buildup on terminals, cables, hold-downs and hoses. Turns pink on contact with battery acid.

Battery Terminal Protector

Used for sealing and coating the terminals of a battery and eliminating the formation of acid salt corrosion that is typically found when terminals are untreated. Prolongs battery life by protecting battery terminals and connectors against moisture and corrosion. Also resists heat aging.



Carb & Choke Cleaner

A blend of solvents specifically formulated to dissolve and remove varnish, gum sludge and clean the residue deposited on carburetors and chokes during the normal operation of a motor vehicle or other gasoline engine powered equipment.

Electrical Parts Cleaner

Quickly dissolves and flushes away grease, oil, dirt and other contaminants while leaving no residue. Use on air conditioning equipment, electric motors, alternators, starting motors, cables, relays, battery chargers and more. NOT SAFE FOR USE ON RUBBER OR PLASTIC.

Contact Cleaner

Removes grease, dirt, oil and other surface contaminants from electrical/electronic devices. Fast drying, leaves no residue and cleans easily. Safe on most surfaces. Extremely flammable.



Penetrating Oil

Prevents rust and corrosion by depositing an ultra thin film that coats and penetrates the surface pores of metal. Penetrates quickly to free rusted bolts, nuts and sliding parts. Displaces moisture to dry out damp electrical parts.



Traditional Gasket Makers



Black RTV Silicone Gasket Maker

O₂ Sensor Safe

Formulated for gasket making applications. Sensor safe and manufactured to meet OEM specifications. Makes instant, leak proof gaskets for all engines, drive train equipment and related components. Temperature resistant up to 500°F (260°C). Resists oil, water, anti-freeze and transmission fluid. Cures tough and flexible. Works on all vehicles.

Red RTV Silicone Gasket Maker

Hi-Temp / O₂ Sensor Safe

Formulated to withstand higher operating temperatures. Sensor safe and manufactured to meet OEM specifications. Resists cracking and migration caused by thermal cycling. Will not leak. Temperature resistant up to 650°F (343°C). Resists oil, water, anti-freeze and transmission fluid.

Blue RTV Silicone Gasket Maker

O₂ Sensor Safe

Replaces most cut gaskets. Sensor safe and manufactured to meet OEM specifications. Resists cracking, shrinking and migration caused by thermal expansion. Cures tough and flexible. Temperature resistant up to 500°F (260°C). Resists oil, water, anti-freeze and transmission fluid. For valve covers, oil pans, transmission pans, rear end housings, timing chain covers, thermostat housing, water pump flanges. Provides exceptional leak control and torque retention.

Clear RTV Silicone Adhesive/Sealant

Provides a transparent, watertight silicone rubber seal for a wide range of applications. Bonds and seals metals, plastic, glass, fabric, vinyl, wood and rubber. Use on windshields, sunroofs, tail lights, interior panels, firewalls and dashboards.

Ordering Information

Dynatex Part No.	Description & Size	Units Per Case
49200	Black Silicone Gasket Maker - 3 Oz. (85gm) Tube - Carded	12
49202	Red Hi-Temp Silicone Gasket Maker - 3 Oz. (85gm) Tube - Carded	12
49203	Blue Silicone Gasket Maker - 3 Oz. (85gm) Tube - Carded	12
49204	Clear RTV Silicone Adhesive/Sealant - 3 Oz. (85gm) Tube - Carded	12
49271	Black Silicone Gasket Maker - 8 Oz. (227g) Automatic Can	12
49272	Red Hi-Temp Silicone Gasket Maker - 8 Oz. (227g) Automatic Can	12
49274	Clear RTV Silicone Adhesive/Sealant - 8 Oz. (227g) Automatic Can	12
49276	Blue Silicone Gasket Maker - 8 Oz. (227g) Automatic Can	12
49290	Black Silicone Gasket Maker - 300ml Cartridge	12
49292	Red Hi-Temp Silicone Gasket Maker - 300ml Cartridge	12
49293	Blue Silicone Gasket Maker - 300ml Cartridge	12
49294	Clear RTV Silicone Adhesive/Sealant - 300ml Cartridge	12

Sealants / Adhesives



Industrial Grade RTV Sealant

A general purpose high quality 100% RTV silicone sealant. The RTV sealant cures to a tough, rubbery solid upon exposure to moisture. This sealant can be applied overhead or on sidewall joints and surfaces without sagging or run off. Use for caulking, sealing, waterproofing and light bonding. Operates in temperatures up to 500°F.



Hi-Tack Gasket Spray

Dries quickly to a highly tacky, elastomeric film. This product was specifically designed to hold the heaviest gaskets in place during assembly. Oxygen sensor safe and highly resistant to automotive fuels and oils. Remains tacky indefinitely and can be applied in advance for convenience in assembly. Has an operating temperature range from -65°F to 450°F (-54°C to 232°C). (80065 Permatex® functional equivalent)

Gasket Remover

Quickly removes baked-on gaskets, silicone, weatherstrip adhesive, carbon deposits, dried oil, adhesives, grease and paint. Removes gaskets in 10-12 minutes and prepares metal parts for new gasket installation.



Ordering Information

Dynatex Part No.	Description & Size	Units Per Case
49280	Clear RTV Silicone Sealant - Industrial Grade - 11 Oz. (312gm Cartridge)	12
49281	Aluminum RTV Silicone Sealant - Industrial Grade - 11 Oz. (312gm Cartridge)	12
49285	White RTV Silicone Sealant - Industrial Grade - 11 Oz. (312gm Cartridge)	12
49286	White RTV Silicone Sealant - Mildew Resistant - 11 Oz. (312gm Cartridge)	12
49289	Clear RTV Silicone Sealant - Marine Grade - 11 Oz. (312gm Cartridge)	12
49297	Black RTV Silicone Sealant - Industrial Grade - 11 Oz. (312gm Cartridge)	12
49358	Hi-Tack Gasket Spray - 12 Oz. Aerosol - 9 Oz. Net Wt.	12
49673	Gasket Remover - 16 Oz. Aerosol - 13 Oz. Net Wt.	12

Brake Maintenance



Brake & Caliper Lubricant

A high performance, high temperature formulated grease that lubricates under the most harmful brake conditions keeping the caliper pins, sleeves, bushings and pistons operating throughout the brake pad life. Prevents corrosion.

Brake System Silicone Compound

A silicone based lubricant that protects rubber and plastic gears. Contains NO petroleum or by-products. Locks out moisture and has excellent wash away resistance. Prevents drying and cracking. Recommended by major brake installer chains, fleets and brake manufacturers. Unaffected by extreme temperatures from -40°F to 500°F.

Ceramic Disc Brake Grease

A pure synthetic, high concentration dry-film, boundary lubricant treated with the latest rust, oxidation and anti-wear additives to provide lasting protection against friction, wear and corrosion. A superior noise dampening compound that will last the life of the brake pads and shoes hence reducing customer comebacks resulting from noise complaints. It will stay in place and protect at extreme temperatures from -50°F to 3000°F. Designed to be compatible with most plastics and rubbers, especially ethylene propylene rubber (EPDM, EP or EPT) commonly used in brake caliper systems. (24125 Permatex® functional equivalent)

Disc Brake Quiet

Forms a high temperature film that absorbs vibration while quieting squeaks and squeals. Can be applied on backing plates, brake pad contact points, on back of brake pads.



Non-Chlorinated Brake & Parts Cleaner

Provides maximum performance in a cleaner without depleting the ozone or hazardous chlorinated solvents. Penetrates through dirt, grease and brake dust. Leaves no residue and dries fast.

Ordering Information

Dynatex Part No.	Description & Size	Units Per Case
49590	Brake & Caliper Lubricant - 8 Oz. Brush Tip Bottle	12
49593	Brake System Silicone Compound - 5.3 Oz. Tube - Boxed	12
1020	Brake System Silicone Compound - 6gm Pillow Packet	1400
49660	Ceramic Disc Brake Grease - Green - 6.75 Oz. Trigger Can w/Brush	6
49661	Disc Brake Quiet - 4 Oz. Squeeze Bottle	12
49662	Disc Brake Quiet - 12 Oz. Aerosol Can - 9 Oz. Net Wt.	12
49665	Non-Chlorinated Brake & Parts Cleaner - 20 Oz. Aerosol Can - 14 Oz. Net Wt.	12

Specialty Greases

Dielectric Grease

A smooth, easily spreadable silicone grease that protects electrical connections and wiring from water, dirt and corrosion (salts, alkalines and magnesium chloride). Maintains its consistency in extreme temperatures from -40°F to +400°F. Displaces moisture, prevents fusing of spark plug wires and prevents voltage leakage. Ideal for transportation and marine industry applications.

White Lithium Grease

A multi-purpose lubricant designed to reduce friction between load bearing, shifting metal surfaces. Great lubricant between metal and plastic surfaces. Protects against rust and corrosion. Increases service life in most moving parts.

Motor Assembly Grease

A lubricant used in rebuilding engines. Dynatex Motor Assembly Grease adheres to component surfaces such as bearings, camshafts, lifters, valves and guides. Once new engine is started the motor assembly grease protects from galling until the regular engine oil arrives.



Red Grease

Multi-purpose lubricant provides extra protection under extreme pressure and temperatures from 0°F to 400°F. Excellent water resistance makes it ideal for machinery operating in damp environments. Use on bearings, automotive hinges, hitches, fifth wheels, cables, pulleys and chains.

Heat Transfer Compound

A grease-like silicone material, heavily filled with heat conductive metal oxides. It is used as a heat transfer medium in the electrical and electronic industry for facilitating heat dispersion. Withstands high and low temperatures (-65°F to 400°F), water resistant, chemically inactive and hydrolytically stable. Use on thermocouple and thermometer wells, mounting semi-conductor devices and thermo joints.

Multi-Purpose Wheel Bearing Grease

A premium, state of the art lithium complex grease. Dynatex Multi-Purpose Wheel Bearing Grease has a high drop point in excess of 500°F, which ensures retention in high temperature applications. This multi-purpose grease has been formulated with a special additive which ensures high film strength, extreme pressure and anti-wear properties.

Ordering Information

Dynatex Part No.	Description & Size	Units Per Case
49611	Red Grease - 16 Oz. Aerosol - 12 Oz. Net Wt.	12
1046	Dielectric Grease - 2gr Pillow Packet	3000
49633	Dielectric Grease - 8 Oz. Brush Top Bottle (08946 3M® functional equivalent)	12
49634	Dielectric Grease - 1/3 Oz. Tube - Carded	12
49635	Dielectric Grease - 5 Oz. Tube - Boxed	12
49636	Dielectric Grease - 2gr Packet - 200 Piece Jar	2
49594	White Lithium Grease - 1.5 Oz. Tube - Carded	12
49595	White Lithium Grease - 16 Oz. Tub NLGI #2	12
49596	White Lithium Grease - 16 Oz. Aerosol Can - 10.5 Oz. Net Wt.	12
49598	Motor Assembly Grease - 6 Oz. Tube	12
49643	Heat Transfer Compound - 5 Oz. Tube - Boxed	12
54016	Wheel Bearing Grease - 1 lb. Tub	12

Repair Adhesives

Auto Seam Sealant

A fast setting, rubber based sealer that has excellent flexibility and tremendous adhesion. Has a self smoothing effect so there is no tooling solvent required. Any fingerprints or sharp edges will completely disappear within 5 minutes after tooling. This product should not be primed unless sealer is completely cured. Any type of paint may be applied after 30 minutes.



Rear View Mirror Adhesive

A professional strength adhesive and activator that secures rear view mirror mounts to windshields. The Rear View Mirror Adhesive adheres to the windshield within 40 seconds and allows mirror mounting in approximately 15 minutes. Easy 1-2 process.

(81840 Permatex® functional equivalent)



4 Minute Epoxy

A rapid curing, general purpose adhesive. It bonds rigid, durable substrates such as metals, ceramics, glass, concrete and wood in all combinations. It forms a clear, hard, rigid, bonding coating in minutes. Pre-measured syringe assures proper mix for consistent results.

(84101 Permatex® functional equivalent)



Muffler & Tailpipe Sealant

A single component, non-slumping sealant that forms a seal that repairs holes and leaks in mufflers, tailpipes and around joints. Secures with heat. Full cure time is 24 hours.

(80335 Permatex® functional equivalent)



Ordering Information

Dynatex Part No.	Description & Size	Units Per Case
49388	Auto Seam Sealant - 11 Fl. Oz. Cartridge	12
49401	Rear View Mirror Adhesive - .6ml Pillow Packet with Primer - Carded	12
49409A	4 Minute Epoxy General Purpose - 1 Oz. Syringe	12
49411	Muffler & Tailpipe Sealant - 4.5 Oz. Tube - Carded	12

Repair Adhesives

GTX Multi-Seal™ Trailer Sealant

VOC Compliant product for all 50 states. GTX takes the place of most traditional sealants (polyurethane/silicone) and is designed to resist all the on-the-road flexing and vibrations. It is fast curing and provides permanent elastic adhesion to most surfaces with excellent elasticity. GTX is non-yellowing, non-streaking, paintable and sandable. Formulated to offer outstanding primerless adhesion to all substrates such as steel, aluminum, glass, vinyl and wood. It can be applied and tooled in almost all weather conditions. Compatible with most paints.



Brush-On Electrical Tape

Outperforms common electrical tape by sealing out moisture and dirt to virtually eliminate corrosion which causes many electrical failures. Sticks to metal, wiring, rubber, vinyl and plastic forming a tough flexible coating that dries at room temperature in 5 minutes. Handy applicator top and thicker formula is great for getting into tight places that just cannot be reached with ordinary tape. Use anywhere a dependable weatherproof connection is required.

(85120 Permatex® functional equivalent)



Super Weatherstrip Adhesive

A versatile trim adhesive widely used in automotive and furniture trim, for bonding vinyl coated fabric and trim fabrics to metal and wood. An air drying contact cement that allows quick bonding yet maintains enough versatility in tack to allow large areas to be spread and bonded at one time. A “product favorite” for the antique car enthusiast.

(81850-BLACK Permatex® functional equivalent)
(81731-YELLOW Permatex® functional equivalent)
(08008-BLACK 3M® functional equivalent)
(08001-YELLOW 3M® functional equivalent)



Ordering Information

Dynatex Part No.	Description & Size	Units Per Case
49390	GTX Multi-Seal Trailer Sealant - Black - 300ml Cartridge	12
49391	GTX Multi-Seal Trailer Sealant - White - 300ml Cartridge	12
49392	GTX Multi-Seal Trailer Sealant - Grey - 300ml Cartridge	12
49412	Black Brush-On Electrical Tape - 4 Oz. Brush Top Can	12
49429	Black Weatherstrip Adhesive - 5 Oz. Tube - Boxed	12
49430	Yellow Weatherstrip Adhesive - 5 Oz. Tube - Boxed	12

Lubricants

Aluminum Anti-Seize

A heavy-duty economical industrial anti-seize lubricant that contains finely divided metallic particles in a special no melt petroleum base grease.
(76732 Loctite® functional equivalent)

Nickel Anti-Seize

A heavy-duty anti-seize lubricant paste containing a balanced blend of pure nickel and graphite, homogenized into a semi-synthetic, non-melting grease base. Does not contain any sulfur, lead, copper, halogens or clay fillers.
(77124 Loctite® functional equivalent)

Copper Anti-Seize

A heavy-duty economical industrial anti-seize lubricant that contains a high concentration of copper metallic particles in a special no melt petroleum base grease. Leaves a protective film that seals and protects metal parts under extreme conditions of heat, pressure, steam and water exposure.
(51147 Loctite® functional equivalent)



Transmission Assembly Lube

A petroleum and hydrocarbon mixture formulated for use as an assembly lubricant for automatic and manual transmissions. Remains stable and smooth at working temperatures, soluble in transmission fluids and will not clog transmission filters. Blue color eliminates misdiagnosing leaks.

Silicone Spray Lubricant

A dry-film lubricant which waterproofs, protects, reduces corrosion, lubricates and extends life of rubber and plastic parts. Suitable for metal, plastic, rubber, vinyl, leather and wood. Active ingredients comply with FDA and USDA regulations.



Ordering Information

Dynatex Part No.	Description & Size	Units Per Case
49550	Aluminum Anti-Seize & Lubricating Compound - 4 Oz. Brush Top Bottle	24
49556	Aluminum Anti-Seize & Lubricating Compound - 6.75 Oz. Trigger Can with Brush	6
49558	Aluminum Anti-Seize & Lubricating Compound - 8 Oz. Brush Top Bottle	12
49560	Aluminum Anti-Seize & Lubricating Compound - 16 Oz. Brush Top Bottle	12
49576	Aluminum Anti-Seize & Lubricating Compound - 16 Oz. Aerosol Can - 12 Oz. Net Wt.	12
49580	Aluminum Anti-Seize & Lubricating Compound - 42 lb. Pail - 5 Gallon	-
49582	Copper Anti-Seize & Lubricating Compound - 8 Oz. Brush Top Bottle	12
49584	Nickel Anti-Seize & Lubricating Compound - 8 Oz. Brush Top Bottle	12
52115	Silicone Spray Lubricant - 16 Oz. Aerosol Can - 10.25 Oz. Net Wt.	12
55016	Transmission Assembly Lube - 1 lb. Tub	12

Pipe / Thread Sealants



Pipe Sealant with PTFE

Provides immediate low pressure sealing performance for tapered pipe threads. This product is designed to cure when in contact with metals fully installed. Lubricates and resists corrosion, prevents leakage, loosening from vibration and moisture in hydraulic, pneumatic, steam and process piping. Allows final adjustment up to 24 hrs. after application. An excellent replacement for pipe dopes and pipe tapes.

(567 Loctite® functional equivalent)

- Seals instantly to moderate pressures
- Fully cures at room temperature to burst pressure of most piping systems
- Will not crack or shrink
- Chemical resistant
- Locks pipe and fittings against vibration
- Contains PTFE

Thread Sealant with PTFE

An all-purpose thread sealant that remains pliable after installation. Can be used on all threaded joints in plastic, aluminum, monel, or stainless steel lines against water, natural gas, LPG, gasoline and others. Temperature range -35°F to 550°F.

- Non-drip formula
- Non-hardening
- Non-toxic
- Good heat resistance
- Contains PTFE
- Resists corrosion



Ordering Information

Dynatex Part No.	Description & Size	Units Per Case
49486	Pipe Sealant with PTFE - 50ml Tube	6
49494	Thread Sealant with PTFE - 4 Oz. Brush Top Bottle	12
49495	Thread Sealant with PTFE - 16 Oz. Brush Top Bottle	6

Super Glue / Adhesives



Super Glue

A fast setting, low to medium viscosity adhesive designed to bond close fitting surfaces quickly. Offers viscosity and flow characteristics that are ideal for filling small gaps. Sets in seconds to form a permanent, transparent bond.

Super Glue Gel

An instant bonding adhesive in a gel form designed to bond close fitting surfaces quickly. Sets in seconds to form a permanent, transparent bond. Supplied as a gel, it may be used on vertical, overhead and hard to reach surfaces.

Use on:

- Metal
- Rubber
- Glass
- Aluminum
- Ceramics
- Vinyl
- Alloys
- Plastics
- Nonporous surfaces

Rubber Toughened Adhesive

A black, high viscosity, rubber toughened ethyl cyanoacrylate adhesive. Provides superior shock and thermal resistance when bonding rubbers, metals and plastics in harsh environments.

Clear Rubber Bonder

A single component, medium viscosity cyanoacrylate adhesive. Suitable for general purpose bonding but provides excellent strength and speed on all rubber compounds.

See our Super Glue "Product Solution" flyer for additional Part Nos.

Ordering Information

Dynatex Part No.	Description & Size	Units Per Case
49403	Super Glue - 3gr Tube - Carded	12
49431	Super Glue - 20gr Bottle	10
49433	Super Glue Gel - 2gr Tube - Carded	12
42241	Black Flexible Rubber Toughened Ethyl Base - 2400 cps - 1 Oz. Bottle	20
45500	Clear Rubber Bonder Ethyl Base - 800 cps - 2 Oz. Bottle	20

Anaerobic Threadlockers

Anaerobic Threadlockers are single component liquids. These adhesives are called anaerobics because they crosslink and cure only in the absence of oxygen. The threadlockers provide a positive seal that resists most liquids. Locks and seals metal threaded assemblies in a wide range of applications. Prevents nuts, bolts and other fasteners from loosening due to vibration. Works in temperatures from -60°F to 350°F (-54°C to 177°C). Fixture tight in minutes. Protects against thread corrosion. *For faster cure times use Dynatex 49674 Primer.*

Blue Medium Strength Threadlocker

Ideal for all 1/4" - 3/4" diameter nut and bolt assemblies. Fills gaps up to .006". Apply prior to assembly and easily removable with hand tools for servicing. Eliminates need for stocking lock nuts and washers. **(242 Loctite® functional equivalent)**

Use on:

- Cup and core plugs
- Starter mounting bolts
- Alternator mounting bolts
- Oil pan bolts
- Intake manifold bolts
- Drive shaft bolts
- Pulley bolts
- Valve cover bolts and more . . .

Red High Strength Threadlocker

Ideal for all 1/4" to 3/4" nut and bolt assemblies where future disassembly is improbable. Fills gaps up to .0008". Applied prior to assembly. **(262 Loctite® functional equivalent)**

Use on:

- Shock absorber bolts
- Frame bolts
- Cylinder block
- Rocker arm studs
- Ring gear bolts
- Fan hub bolts

Green High Strength Threadlocker

Ideal for all threaded assemblies less than or equal to 1/2". It can also fill porosity in welds, castings and powder metal parts. Because of its low viscosity and capillary action, it *wicks* between threads and eliminates the need to disassemble and reassemble. **(290 Loctite® functional equivalent)**

Use on:

- Seal brazed joints in cooling systems
- Seal porous welds
- Seal porosity on brake unit housings

Purple Low Strength Threadlocker

Ideal for all nut and bolt fasteners under 1/4" that require occasional adjustment. Easily removable with hand tools for servicing. **(222 Loctite® functional equivalent)**

Use on:

- Small bolts in distributor
- Dash board assembly bolts
- Relay lock screws
- Idle control screws
- Small bolts in ignition systems
- Throttle body assembly bolts
- Set screw for rear view mirror

Ordering Information

Dynatex Part No.	Description & Size	Units Per Case
9442	Blue Threadlocker - Medium Strength - 1ml Tube	100
49440	Blue Threadlocker - Medium Strength - 10ml Bottle	20
49441	Blue Threadlocker - Medium Strength - 6ml Tube - Carded	6
49442	Blue Threadlocker - Medium Strength - 24ml Bottle - Carded	6
49443	Blue Threadlocker - Medium Strength - 50ml Bottle	10
49444	Blue Threadlocker - Medium Strength - 250ml Bottle	4
49446	Blue Threadlocker Gel - Medium Strength - 35ml Pump Bottle	6
9440	Red Threadlocker - High Strength - 1ml Tube	100
49450	Red Threadlocker - High Strength - 10ml Bottle	20
49451	Red Threadlocker - High Strength - 6ml Tube - Carded	6
49452	Red Threadlocker - High Strength - 24ml Bottle - Carded	6
49453	Red Threadlocker - High Strength - 50ml Bottle	10
49454	Red Threadlocker - High Strength - 250ml Bottle	4
49456	Red Super Threadlocker Gel - High Strength - 35ml Pump Bottle	6

Anaerobic Threadlockers



Green High Strength Sleevelocker

Ideal for all nut and bolt assemblies less than 1/2". Because of its low viscosity and capillary action, it *wicks* between threads and eliminates the need to disassemble and reassemble. **(640 Loctite® functional equivalent)**

Use on:

- Cylinder sleeves
- Bearings and bushings
- Woodruff keys
- Valve guides
- Valve seats
- Liner assemblies

Threadlocker Gel Pump (Red & Blue)

- Ideal for all 1/4" - 1" diameter nut and bolt assemblies
 - Temperature resistance range -75°F to 300°F (-59°C to 149°C)
 - Easy to use self-metering pump eliminates waste
 - Easy to apply
 - No drips - stays where it is applied
 - No mess
 - Easy cleanup
- (248/268 Loctite® functional equivalent)**



Anaerobic Gasket Maker

Provides a tough, resilient, solvent and temperature resistant seal that flexes with flange movement caused by vibration, pressurization or thermal changes all while retaining flexibility for proper gasketing. Non-corrosive to aluminum and cast iron. No curing outside of joint. **(515/518 Loctite® functional equivalent)**

Use on:

- Vacuum pump flanges
- Fuel pumps
- Water pumps
- Gearbox covers
- Automotive and truck axle covers

Threadlocker Primer

A highly reactive surface activator designed to speed cure rates of *Dynatex Anaerobic Adhesives*. It is designed for use in bonding applications where speed is essential. Parts should be as clean as possible before application to ensure optimal adhesive performance, but this primer can also act as a cleaner in situations where part preparation is impossible. **(9649 Loctite® functional equivalent)**

Ordering Information

Dynatex Part No.	Description & Size	Units Per Case
49460	Green Threadlocker - High Strength - 10ml Bottle	20
49463	Green Threadlocker - High Strength - 50ml Bottle	10
49472	Green Sleevelocker - High Strength - 24ml Bottle - Carded	6
49474	Green Sleevelocker - High Strength - 250ml Bottle	4
49482	Purple Threadlocker - Low Strength - 24ml Bottle - Carded	6
49477	Red Anaerobic Gasket Maker - High Strength - 50ml Tube	10
49674	Threadlocker Primer - 6 Oz. Aerosol Can - 5.5 Oz. Net Wt.	6